
COMPACK CP 350 PLUS

vertical form, fill and seal machine







- Stainless steel; hygienic design
- Robust building quality
- Modular construction
- Allen Bradley PLC and electrical components
- Servo driven film transport for accurate bag length
- Ergonomic film support with film tensioning and brake









COMPACK CP 350 PLUS

vertical form, fill and seal machine

Vertical form, fill and seal machines create bags from a flat film from the reel. The machines are suitable for packing many types of food and non food products.

The Compack CP 350 PLUS has a hygienic design and is constructed out of stainless steel. Together with the open construction it makes the machine very easy to clean. Due to its low height and small footprint the machine is very versatile, both in small production areas as well as in industrial environments. Besides working with various weighing and dosing systems, the CP 350 PLUS is also very suitable for manual filling.


With its large range in pack sizes (75 up to 350 mm bag width and unlimited bag length) and a capacity up to 40 bags per minute, this machine can be used in a wide variety of packaging situations. In the standard configuration it produces pillow bags. Optionally the machine can also produce self standing bags.

The modular construction guarantees that each module can be exchanged within minutes. This creates a reduction in downtime and costs during maintenance work. Options and components can be retrofitted easily and quickly.

Machine is standard equipped with:

- Stainless steel construction; hygienic design
- ☆ Machine safety according to CE regulations
- Allen Bradley PLC with 7" full color touchscreen and 99 programs can be created and stored
- Pneumatic opening and closing of the servo driven film pull belts
- ☆ Ergonomic film support with film tensioning and brake
- ☆ Cover plate over the entire machine
- ☆ Low power and air consumption
- ☆ Machine in mobile frame

| CP 350 | PLUS |
|----------------------|----------------------|
| √ í | . <u>Г</u> |
| $\overline{\square}$ | ☒ |
| $\overline{\square}$ | $\overline{\square}$ |
| $\overline{\square}$ | $\overline{\square}$ |
| | \square |
| | \square |
| | \square |
| | \square |
| \square | \square |
| | \square |
| | |



CP 350 PLUS 1.495 962 1.647 575 mm

Technical specifications CP 350 PLUS:


Various weighing and dosing systems Customer specific options on request

| Bag width (pillow) | 75 - 350 | mm |
|----------------------------------|----------------|-------|
| Max. bag length | unlimited | mm |
| Max. bag length per sealing step | 230 | mm |
| Max. production speed | 40 bags/min | |
| Film thickness | 25 - 120 | μ |
| Core diameter | 76 (3") | mm |
| Max. film width | 750 | mm |
| Max. outer diameter film roll | 320 | mm |
| Voltage | 230 V, 50/ | 60Hz |
| Power during production | 1.200 | Watt |
| Air consumption | 6 bar, 150 ltr | r/min |

All dimensions and specifications are indications based on standard set up. Final details depend on customer specifications









GKS Packaging b.v. Steenoven 18 5626 DK Eindhoven (NL)

+31 (0)499 463011 sales@gkspackaging.com